

TIPO	DENSITÀ	RESISTENZA ALLA COMPRESIONE	INDENTAZIONE			RESA ELASTICA	CARICO A ROTTURA	PERDITA DI PORTANZA A FATICA DINAMICA	DEFORMAZIONE PERMANENTE COMPRESIONE AL		COLORE	LARGHEZZA	COMPORTAMENTO AL FUOCO SECONDO LE NORME	CERTIFICAZIONI CERTIFICATION
TYPE	DENSITY	COMPRESSION LOAD DEFLECTION	IDENTATION LOAD DEFLECTION			BALL REBOUND	TENSILE STRENGTH	DYNAMIC FATIGUE	COMPRESSION SET		COLOUR	WIDTH	FLAME TEST ACCORDING TO	
	kg/m ³ ±5%	40% kPa ±15%	N ±15%			% ±10%	kPa (min.)	(Max%)	50% (Max%)	75% (Max%)		mm (-0 /+40)		

SERIE CMHR

T 25/M CM	26,5	1,5	45	60	130	51	65	28	9,0	12,0	TB	2100	A*•B•C•D•E•G•I	1•3
T 25 CM	27,5	3,5	95	130	260	43	100	34	11,0	16,0	BN	2100	A*•B•C•D•E•G•I	1•3
T 30/P CM	30	3,7	100	140	290	43	110	32	9,0	14,0	BN	2100	A*•B•C•D•E•F•G•I	1•3
T 40 CM	40	4,2	125	170	340	55	120	24	4,5	6,5	GL	2100	A*•B•C•D•E•F•G•I	1•3
T 40/P CM	40	5,2	145	205	430	50	135	28	6,0	9,0	GL/AN	2100	A*•B•C•D•E•F•G•I	1•3
ELAST PF 30 FR	30	2,2	65	85	175	56	100	23	5,5	7,5	GL	2100	A*•B•C•D•E•G•I	1•3
ELAST PF 35 FR	35	2,3	70	95	190	60	105	20	5,0	7,0	RS	2100	A*•B•C•D•E•G•I	1•3
ELAST PF 40/P FR	40	3,2	95	125	255	63	105	18	3,5	4,5	TC	2100	A*•B•C•D•E•G•I	1•3
ELAST PF 45 FR	45	2,8	85	115	230	66	90	16	3,0	4,0	AR	2100	A*•B•C•D•E•G•I	1•3
ELAST PF 50 FR	50	4,3	130	175	360	66	115	16	2,5	3,5	BN/RS	2030	A*•B•C•D•E•G•I	1•3
ELAST PF 50/P FR	50	6,3	170	230	510	52	140	24	4,0	5,0	GP	2100	A*•B•C•D•E•G•I	1•3
ELAST PF 55 B1	54	5,3	160	205	410	66	130	16	2,5	3,5	BN	2100	A*•B•C•D•E•G•I•L	1•3
ELAST PF 65 FR	60	7,5	215	290	640	55	150	22	3,5	4,5	BN	2100	A*•B•C•D•E•F•G•I	1•3

CME STANDARD

T 25 CME	28	4,0	115	155	320	38	70	38	5,0	8,0	TB	2100	B•C•D•E•G•I	1•3
T 30 CME	30	4,2	125	165	330	40	80	36	4,0	6,0	TB	2100	B•C•D•E•G•I	1•3

COMPORTAMENTO AL FUOCO SECONDO LE NORME / FLAME TEST ACCORDING TO:

A* - CALIFORNIA TECHNICAL BULLERIN 117/2013 - Section 3

Schiume poliuretaniche additivate con ignifugante liquido base Fosforo/Cloro, vietate in California dal 01/01/2020.

Foams containing Phosphorus/Chlorine liquid flame retardant, banned in California from 01/01/2020.

B - MVSS MOTOR VEHICLE SAFETY STD 302

C - FAR./JAR./CS.25.853 - Appendix F Part I - (a) (1) (ii)

D - ARRÊTÉ DU 21 NOVEMBRE 2002 CLASSEMENT M4 (NFP 92-507:2004)

E - UNI 9175 (CLASSE 1 IM)

F - AIRBUS ATS 1000.001 - ABD 0031

G - FTP CODE 2010 Annex 1 Part 8 (ex IMO Resolution A 652(16))

I - SCHEDULE 1 PART I OF THE FURNITURE AND FURNISHINGS (FIRE) (SAFETY) REGULATIONS 1988, AMENDED 1989 AND 1993 (B.S. 5852: PART 2 CRIB V)

L - DIN 4102-B1

Le schiume riportate in verde vengono prodotte solo su ordine con quantitativi minimi e per consegna in un arco di tempo limitato. I prodotti in nero sono disponibili a magazzino.
The foams marked in green are produced only on order with minimum order quantities and a limited time frame for delivery. The products in black are available on stock.